



SMT-4344

43" UHD LED Monitor



Key Features

- 43 inch UHD Monitor, support up to 3840×2160@60Hz
- Brightness 300 cd/m² (Typ), Contrast 1000:1 (Min) 1200:1 (Typ)
- Viewing Angle (H/V) : 178°/178°, Response Time : 8ms(Typical)
- Video Input : HDMI 2.0(2), DP1.4(1), two windows PIP/PBP
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

Compatible Accessories (Optional)



SBM-4343

SMT-4344

43" UHD LED Monitor



Specifications

Display		
Type	LED Monitor	
Screen Size	43"	
Max. Resolution	3840*2160	
Brightness	250 cd/m ² (Min), 300 cd/m ² (Typ)	
Contrast Ratio	1000:1 (Min) 1200:1 (Typ)	
Aspect Ratio	16:9	
Viewing Angle (H/V)	178°/178°	
Display Color	1.07G (8bits + FRC)	
Response Time	8ms(Typ)	
Panel Life	30,000 hours	
Interface		
Video	Connectors	HDMI 2.0(2), DP 1.4(1), two Windows PIP/PBP
HDMI	Connector	HDMI
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 2560 x 1440@60Hz, 3840 x 2160@60Hz, 3840 x 2160P@30/50/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
DP	Connector	DP
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 2560 x 1440@60Hz, 3840 x 2160@60Hz, 3840 x 2160P@30/50/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
Audio	Connector	Audio Out
	Output Signal	Speakers :8Ω 6Wx2
Application Support	Remote Controller	
On Screen Display		
Functions	VESA™ DPM Compatible	
Language	Korean, English, Русский, Deutsch, Français, Español, Italiano, Português, Chinese (Simplified), Chinese (Traditional), Japanese, Arabic	
General		

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com.

Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	<80W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions without Stand (WxHxD)	967*560*73.5mm
	Weight	8.2Kg
	Cabinet Color	Black
	VESA Mounts Interface	100*100mm /400*200mm